

FICHE TECHNIQUE - TECHNICAL SHEET

COMPENSATEUR NBR AVEC RACCORD UNION BRONZE NBR



- CORP EN NITRILE
- TEMPERATURE : -15°C + 90°C
- POUR FLUIDES : EAU, EAU DE MER, GAZOIL

Diametro nominale Nominal Diameter		Lunghezza di install. Installed lenght mm.		Corsa mm. Travel mm.	Movimenti ammissibili Allowable movements from neutral				Pressioni a 80°C Pressions 80°C		
Ø pollici inch		Lungh. libera	Minima Massima	Tot. compressione estensione	Compr. assiale	Estens. assiale	Corsa laterale	Corsa angolare	Positiva PSIG	Positiva kg/cm2	Negativa mm HG
		Natural lenght	Minimum maximum	Total compressed extended	Axial Compr.	Axial Extension	Lateral deection	Angular deection	Positive PSIG	Positive kg/cm2	Negative mm HG
3/4"	20	203	186 - 206	181 - 209	22	6	22	32°	150	10	660
1"	25	203	186 - 206	181 - 209	22	6	22	25°	150	10	660
1" 1/4	32	203	186 - 206	181 - 209	22	6	22	25°	150	10	660
1" 1/2	40	203	186 - 206	181 - 209	22	6	22	20°	150	10	660
2"	50	203	186 - 206	181 - 209	22	6	22	15°	150	10	660
2" 1/2	65	240	224 - 244	218 - 246	22	6	22	12°	150	10	660
3"	80	240	224 - 244	218 - 246	22	6	22	10°	150	10	660